

JK RockGuard Rear Bumper



Important Notes:

Prior to beginning this or any installation read these instructions to familiarize yourself with the required steps and evaluate if you are experienced and capable to personally perform these modifications.

Refer to the parts list to ensure that all necessary components and hardware has been included. If any parts are missing please contact your local retailer for assistance.

Warning: Bumpers are heavy. Make sure you have a suitable jack or a friend or two to help with removal and installation.

Kit Contents

Item ID	Item Description	Quantity
4604100	Hardware Pack: 4-3/4"x1.5" and 4-3/4" Flat Washers	1
654100	Rear Bumper	1
654101	Clevis Mounts	2

Tools Needed

Metric Sockets: 16mm
 Metric Wrenches: 16mm
 Standard Wrenches: 1 1/8"

TERAFLEX PRODUCT INSTALLATION GUIDE

TeraFlex, Inc.
 5680 W Dannon Way
 West Jordan, UT 84081
 Phone/801.288.2585
 Fax/801.713.2313
www.teraflex.com

Revised: 27-Jun-12


1. Support the rear bumper and begin by removing the 4 bolts that attach small brackets from the body to the bumper. These brackets are directly under the tailgate on the passenger and driver sides. Remove the remaining 4 bolts, 2 on the driver side frame rail and 2 on the passenger side frame rail, and remove the bumper.

Note: The 2 brackets and the 8 factory bolts that are removed in step 1 will be re-used to attach the new Teraflex RockGuard Bumper, DO NOT DISCARD.

2. Make sure 2 factory bolts are in reach on both sides of the Jeep.
3. Lift and slide the bumper into place and align the 2 smaller holes with the factory bolt holes. Insert the factory bolts and finger tighten.
4. Insert the clevis mounts into the cutouts of the bumper and into the frame.
5. Use a jack or appropriate lifting device to help align the the bumper with the larger holes in the frame.
6. Once the bumper is aligned with the holes in the frame, move the clevis mount into place and insert a 3/4" bolt with a washer into the hole farthest away from the Jeep and finger tighten. Insert and finger tighten the remaining 3/4" bolt.



7. Repeat step 6 on the opposite side of the Jeep.
8. With the remaining 4 bolts, replace the factory brackets to the same location they were removed and tighten the bolts.



Note: There is some "play" in the bumper after all the bolts are installed and finger tight. This is to allow room for slight variations in mounting points from Jeep to Jeep. Visually inspect the bumper and adjust and align if needed.

9. When satisfied with the alignment of the bumper, begin tightening each bolt to the specifications below.
10. Your new TeraFlex RockGuard Bumper is now successfully installed.

Torque Specifications

- 3/4" Bolt - 120 ft/lbs
- Factory 10mm Bolts - 40 ft/lbs



PRODUCT INFORMATION

MAINTENANCE INFORMATION:

It is the buyer's responsibility to have all suspension, drivetrain, steering, and other components checked for proper tightness and torque after the first 100 miles and every 3000 miles after that.

NOTICE TO INSTALLER:

The enclosed "Warning to Driver" sticker must be installed in the vehicle in driver's view. This sticker is to act as a constant safety reminder when operating the vehicle. It is your responsibility as the equipment installer to install the provided sticker and to forward the product instructions to the vehicle's owner for review. If a "Warning to Driver" sticker or product installation guide were not included in the kit, FREE replacement stickers and instructions are available by request. It is the installer's duty to ensure a safe and controllable vehicle after the modifications have been performed.

WARNING:

Neither the seller nor the manufacturer will be liable for any loss, damage, or injury directly or indirectly arising from the use of or inability to determine the use of these products. Before using, the user shall determine the suitability of the products for its intended use, and the user shall assume all responsibility and risk in connection therewith.

WARNING TO DRIVER:

This vehicle has been modified to enhance off road performance and has unique handling characteristics. Use in harsh environments can cause extreme stress on the components. Vehicle should be inspected after being off road to make sure that all the components are in working order and safe to travel on the highway. All fasteners should be checked so that they are at the correct torque specifications as the vibration and stresses from off-roading may cause critical fasteners to work loose. Extra care should be taken to inspect the critical components, steering, and brake systems. During each oil change components such as arms, tie rod ends, etc. should be greased and checked for excessive wear. Any worn components should be replaced. When returning to the pavement always set or restore tire air pressure to the factory recommendation and connect or engage any disabled sway bar mechanisms. Because of the higher center of gravity and larger tires, this vehicle handles and reacts differently than many passenger cars, both on and off road. You must drive it safely! Extreme care should be taken to prevent vehicle rollover or loss of control, which can result in serious injury or death. Avoid sudden sharp turns or abrupt maneuvers. Generally, braking performance and capabilities are decreased when significantly larger/heavier tires are used, especially when used in combination with transfer case low-range reduction kits. Take this into consideration while driving. Do not add, alter or fabricate any factory or aftermarket parts to increase vehicle height over the intended height of the TeraFlex product purchased. Mixing component brand is not recommended. TeraFlex Inc. will not be responsible for any altered product or any improper installation or use of our products. We will be happy to answer any questions concerning the design, function, and correct use of our products. It is ultimately the buyer's responsibility to have all bolts/nuts checked for tightness after the first 100 miles and then every 3000 miles. Wheel alignment, steering system, suspension and drive line systems must be inspected by a qualified professional mechanic at least every 3000 miles.

TERAFLEX PRODUCT WARRANTY:

Tera Manufacturing warrants TeraFlex Suspension products to the original retail purchaser to be free of defects in material and workmanship for as long as the original purchaser owns the vehicle on which products were originally installed. Failure to complete regular maintenance (grease every 3000 miles) on TeraFlex FlexArms will void this warranty. All other conditions of the standard TeraFlex product warranty apply.

All TeraLow products are covered by TeraFlex's two (2) year warranty to be free of defects in material and workmanship for two years from date purchased.

Tera axles are covered by a 12-month warranty to be free of defects in materials and workmanship. This warranty does not cover or include product finish, improperly installed or applied products, improperly maintained products, products or components used for racing or competition or damage due to abuse or neglect, products that fail due to the use of larger tire and wheel combinations.

All returns must be accompanied by an original invoice. It is the customer's responsibility to remove the product from the vehicle. Shipping charges are the responsibility of the customer. Tera Manufacturing will pay the return freight if the product meets the terms of warranty.

This warranty is for the replacement or repair of defective TeraFlex products only and does not include freight charges, labor charges for removal of or installation of TeraFlex or related products or components, costs incurred due to down time of the vehicle, or lost profits due to vehicle down time.

A returned goods authorization number (RGA#) must accompany any returned products. For more information please contact a TeraFlex customer service representative.

COPYRIGHT

©Copyright 2008. All rights reserved, TeraFlex Inc. Reproduction of this catalog and/or any of its contents without written permission is strictly prohibited.

TeraFlex® is a registered trademark of TeraFlex Inc. All trade names and logos including but not limited to TeraFlex, FlexArms, RockGuard, Monster, and LCG are protected by law and duplication of trade names and/or logos are strictly prohibited.

TeraFlex Inc. reserves the right to update, discontinue, redesign, modify finish, part number or component build parts if deemed necessary without written notice. TeraFlex Inc., and any associated dealers are not responsible for misprints or typographical errors that may have inadvertently been made within this instruction sheet.

Jeep® and the Jeep® grill are registered trademarks of Chrysler LLC, and have no affiliation with TeraFlex Inc.