



General Installation Instructions

Applying your new decal is a very simple process but make sure to take your time. Below are some tips to help make the installation process go a little smoother. Please read them completely before you start.

Tools needed:

Rubbing alcohol
Squeegee with felt edge or a credit card wrapped in a towel or microfiber cloth (wrapped to prevent scratches)
Spray bottle with soapy water (a drop or two of liquid dish soap in a 16oz spray bottle)
Microfiber cloth
Razor blade (only needed if mounting holes are present)
Hair Dryer/Heat Gun (optional)

Installation Steps:

Step 1: Thoroughly clean area of all debris using rubbing alcohol and/or soap and water.

Step 2: Using the soapy water, spray the area where the decal will be installed. (More is better!)

Step 3: Spray the back of the decal. Pro tip – Spray your fingertips too so the decal doesn't stick to your hands. This makes it easier to apply.

Step 4: Apply decal.

Step 5: Once the decal is centered, use the squeegee to flatten the decal and remove all bubbles and liquids from underneath.

(if there is no room for a tool use your finger to contour the decal into place)

(if the decal isn't sticking allow it to dry a bit, it becomes more tacky as it dries)

(if wrinkles are in the material, apply light heat from a hair dryer/heat gun will relax the vinyl)

(if mounting holes are present cut an 'X' using a razor and fold the flaps into the hole and affix)

Step 6: Let it sit over night to fully adhere

Disclaimer: Vinyl films and the adhesives that allow them to adhere to your vehicle work best at room temperatures when installing. Affixing a vinyl wrap is more difficult than ordinary decals, as with any automotive project please research anything you plan to install on your vehicle. Products damaged during installation are the responsibility of the installer. Damaged or installed products cannot be returned or refunded.